

# Klarion™ EGS 6020

## TECHNICAL SPECIFICATIONS

	Klarion Cleaner	Klarion Sanitizer
<b>Base System</b> (Does not include storage tanks)	30.25" x 30.25" x 79" (77 cm x 77 cm x 200 cm)	
<b>Functionality</b>	Generate ECA solutions on-site	
<b>Intended Use</b>	Multi-purpose cleaner	Sanitizer/Disinfectant
<b>Output</b>	1.0 - 1.5 gpm (4.0 - 5.5 lpm)	0.6 gpm (2.3 lpm)
<b>Operating Voltage</b>	100-240VAC, 50/60Hz, single phase	
<b>Power Consumption</b>	0.7 kW	
<b>Salt Consumption</b> (Not including water softener)	Approx 0.3 lbs/hour (0.14 kg/hr)	
<b>Salt Purity</b>	99.9% NaCl	
<b>Water Hardness Requirement</b> (Achieve with included water softener)	< 1 grain/gallon	
<b>Iron Content Requirement</b>	< 0.3 mg/l (ppm)	
<b>Chemical Contents</b>	< 0.06% Sodium Hydroxide > 99.94% Water	> 0.0165% Hypochlorous Acid < 99.9835% Water
<b>pH</b>	10.5 - 12.5	5 - 6
<b>Free Available Chlorine Content</b>	–	> 165 mg/l (ppm)



From *Spraying Systems Co.*

### CONTACT US FOR MORE INFORMATION

North Avenue and Schmale Road, P.O. Box 7900, Wheaton, IL 60187-7901 USA

Tel: 1.630.517.1010

info@klarion.com

[www.klarion.com](http://www.klarion.com)